



An inspection certificate is supplied as standard. Refer to page U-11 for details.

Dial Indicators

Comparison measuring instruments which ensure high quality, high accuracy and reliability.

SERIES 2 — Standard Type, Inch Reading

SPECIFICATIONS

Inch		ANSI/AGD type							
Order No.		Graduation (in)	Range (range/rev) (in)	Accuracy (in)			Repeat-ability (in)	Dial reading	Measuring force (N)
w/lug	Flat-back			First 1 Rev/2.5 Rev/10 Rev	Retrace				
2414S	2414SB	0.001	0.5 (0.1)	±0.001/±0.001/±0.001	0.0002	±0.0002	±0-100	1.8 or less	
2415S	2415SB	0.001	0.5 (0.1)	±0.001/±0.001/±0.001	0.0002	±0.0002	0-50-0	1.8 or less	
2914S	2914SB	0.001	0.5 (0.1)	±0.001/±0.001/±0.001	0.0002	±0.0002	100-0	1.8 or less	
2506S	2506SB	0.0005	0.125 (0.05)	±0.0005/±0.0005/—	0.00016	±0.0001	±0-50	1.8 or less	
2507S	2507SB	0.0005	0.125 (0.05)	±0.0005/±0.0005/—	0.00016	±0.0001	0-25-0	1.8 or less	
2514S	2514SB	0.0005	0.5 (0.05)	±0.0005/±0.0005/±0.0015	0.00016	±0.0001	±0-50	1.8 or less	
2922S	2922SB	0.0005	0.125 (0.05)	±0.0005/±0.0005/—	0.00016	±0.0001	0-25-0	1.8 or less	
2356S-10	2356SB-10	0.0001	0.25 (0.01)	±0.0002/±0.0002/±0.0003/±0.0004 (First 20rev)/±0.0005 (Over 20rev)	0.0001	±0.00003	0-10	2.0 or less	
2358S-10	2358SB-10	0.0001	0.5 (0.01)	±0.0002/±0.0002/±0.0003/±0.0004 (First 20rev)/±0.0008 (Over 20rev)	0.00015	±0.00003	0-10	2.0 or less	
2802S-10	2802SB-10	0.0001	0.025 (0.01)	±0.0001/±0.0001/—	0.0001	±0.00003	0-10	2.0 or less	
2803S-10	2803SB-10	0.0001	0.025 (0.01)	±0.0001/±0.0001/—	0.0001	±0.00003	0-5-0	2.0 or less	
2804S-10	2804SB-10	0.0001	0.05 (0.01)	±0.0001/±0.0001/±0.0002	0.0001	±0.00003	0-10	2.0 or less	
2805S-10	2805SB-10	0.0001	0.05 (0.01)	±0.0001/±0.0001/±0.0002	0.0001	±0.00003	0-5-0	2.0 or less	
2905S-10	2905SB-10	0.0001	0.05 (0.01)	±0.0001/±0.0001/±0.0002	0.0001	±0.00003	10-0	2.0 or less	
2923S-10	2923SB-10	0.0001	0.05 (0.01)	±0.0001/±0.0001/±0.0002	0.0001	±0.00003	0-5-0	2.0 or less	

Note: Completed products inspection is performed in the vertical orientation (contact point downward) and the stated accuracy is guaranteed.

FEATURES

Inch				
Order No.				
w/lug	Flat-back			
2414S	2414SB			
2415S	2415SB			
2914S	2914SB		✓	
2506S	2506SB			
2507S	2507SB			
2514S	2514SB			
2922S	2922SB			
2356S-10	2356SB-10			✓
2358S-10	2358SB-10			✓
2802S-10	2802SB-10	✓		✓
2803S-10	2803SB-10	✓		✓
2804S-10	2804SB-10	✓		✓
2805S-10	2805SB-10	✓		✓
2905S-10	2905SB-10	✓	✓	✓
2923S-10	2923SB-10	✓		✓

Dial Indicators

Comparison measuring instruments which ensure high quality, high accuracy and reliability.

DIMENSIONS

